

LUMBERKOTE LK5G SAFETY INFORMATION

COMPANY IDENTIFICATION

Intech Anchoring Systems
8250 Bunkum Rd, Caseyville, IL 62232
800-223-7015

Emergency Telephone INFOTRAC: 800-535-5053

IDENTIFICATION

Product Identifier:

Product Name:

LumberKote CS.
LumberKote CC.

Other Means of Identification:

Part Number:

Synonyms:

LK5G.
Watson Seal.

HAZARDS IDENTIFICATION

Considered Non-Toxic

Health:	0.
Flammability:	0.
Reactive:	0
Special:	None.

For Professional Use Only.

Product and Tints used are considered Non-toxic if product is used as directed.

- (1) Exposure limit as a nuisance dust. A dust hazard is not expected during normal usage of this product. A dust hazard is considered if sanding product off surfaces.
- (2) Product contains 4% Zinc Oxide for film protection and are not considered hazardous.
- (3) Product use-Sealant for Wood and Concrete Block
- (4) Independent Testing of base component- Block Environmental, K-Prime, Test America, LabThink, Underwriters Laboratory WERC Smart-International verified and listed. Tint is nationally listed (Abbey Color)
- (5) USGBC LEED Points - up to 3 or 4.5 for low emitting coatings

COMPOSITION / INFORMATION ON INGREDIENTS

Trade Secret claimed, colorant use is Patent Pending.

FIRST-AID MEASURES

Do not ingest or inject-if injected or ingested- seek medical attention immediately.



LUMBERKOTE[™]

Eye wash for 15 minutes if contact occurs. Seek medical attention if irritation exists.
Wash from skin, hair or objects while product is wet, product once dried is difficult to remove.

FIRE-FIGHTING MEASURES

Non-Flammable. No hazards expected. Normal smoke and carbon fumes exist if burned. ABC Extinguisher recommended. Flash point is 174 degrees. Rating #4.

ACCIDENTAL RELEASE MEASURES

Cleanup spills using wet paper towels or mop, dispose of paper towels in trash bins, rinse mop after cleanup with water.

Do not dump, pour or release product into lakes or streams. Safe for Landfill disposal.

HANDLING AND STORAGE

Store in a dry area away from sunlight. Keep container closed. Protect from freezing.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Wear proper eye protection, approved particulate paint mask, hair protection, old clothing when opening container, mixing, pouring, and applying this liquid product. Keep Children and Pets away from working area, and away from open containers and equipment. Keep containers tightly close to prevent accidental drowning. Observe OSHA Guidelines and rules. Keep away from electrical contact and fixtures as contact with electrical power may result in electrical shock or death. Ventilate while applying product. Follow label directions.

PHYSICAL AND CHEMICAL PROPERTIES

Non-Toxic. Slightly white in color-semi-transparent, slight sweet odor. Tinted product may be orange in color appearance.

STABILITY AND REACTIVITY

Protect from freezing. Non-reactive, Stable. Do not thin mixture with oil or thin with water or induce any additional product.

TOXICOLOGICAL INFORMATION

Non-toxic when dry. No Leaching. Will not affect termite bait or pesticide liquids. Transparency of dried film allows for Lumber Mill Markings and Termite inspections to be made.

ECOLOGICAL INFORMATION* (NON-MANDATORY)

Non-Toxic to aquatic life or animals, Fresh water or Saltwater if used as directed.

DISPOSAL CONSIDERATIONS* (NON-MANDATORY)

Regular trash disposal and landfill disposal recommended.
Recycle containers.

TRANSPORT INFORMATION* (NON-MANDATORY)

Not DOT/Hazardous or dangerous goods. Class 60.



LUMBERKOTE™

REGULATORY INFORMATION* (NON-MANDATORY)

Not regulated by any agency. Not intended for use as a Pesticide.

OTHER INFORMATION

Date prepared or updated- March 2019

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release, and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state, or provincial, and local laws.



LUMBERKOTE™